



1	C86	"H": 6800 series; "L": 8080 series
2	VSS	Power ground
3	VDD	Power supply (+3.3V)
4	DB7(scl)	DATA BUS 7(serial data)
5	DB6(scl)	DATA BUS 6(serial clock)
6	DB5	DATA BUS 5
7	DB4	DATA BUS 4
8	DB3	DATA BUS 3
9	DB2	DATA BUS 2
10	DB1	DATA BUS 1
11	DB0	DATA BUS 0
12	/Rd(E)	Read signal
13	/WR(R/W)	Write signal
14	A0	H:data; L: instruction
15	/RES	Reset signal
16	/CS1	Chip select
17	A	Backlight (+) +3.3V
18	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 12:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
8. CONTROLLER: ST7567
9. BACKLIGHT TYPE: WHITE
10. BACKLIGHT SUPPLY VOLTAGE: +3.3V



WAYING (HONGKONG) SHARES LIMITED

DESIGN:

MODEL NUMBER:

UNITS: MM

CHECK:

WYM12864K29

VERSION: A

APPROVE:



SHEET: 1 OF 1

Unspecified tolerances are ±0.3

DATE: 2013-04-18